

75W SV750 HALOGEN ILLUMINATOR

FIBER OPTIC LIGHT SOURCE



For use with End Light PMMA cable. Applications include starry ceilings, special effects, fiber optic lighting fixtures, architectural models.

Technical Information:

Lamp Type: 75 Watt, MR16 Quartz Halogen **Lamp Life:** 4,000 hours average rated life

Power Consumption: 88 watts max **Electrical:** 120V 60Hz / .70 Amps

Chassis: Powder Coated

Dimensions: 5.5" X 9.5" X 5.75" (140mmX241mmX146mm)

Weight: 7 lbs. (3.2kg)

Fiber Capacity: 2500 x 0.75mm PMMA end light fibers

Color/Twinkle Wheel:

- Twinkle Wheel
- 4 position – Clear, Magenta, Lime Green, Cyan
- 8 position – Clear, Cyan, Yellow, Turquoise, Orange, Dark Blue, Magenta, Lime Green

Mounting: Surface or wall mount **Mounting Clearance:** 24" all sides **Ventilation:** 21 CFM

IP Rating: 20 **dB Rating:** 40dba

Operating Temperature Range: Min. -20°F (-29°C) Max. 110°F (44°C)

Warranty: 2 years on parts, excluding lamp **Certs:** UL Listed Dry location

Ordering Info:

Stock No.	Description
SV750	75 W Halogen Illuminator
TW	Twinkle Wheel
CW4	4 Position Color Wheel Std.
CW8	8 Position Color Wheel Std.

Vivid Light Design