

# 150W TOWER 150T METAL HALIDE ILLUMINATOR

## FIBER OPTIC LIGHT SOURCE

**Technical Data:**

**Lamp Type:** 150 Watt, Metal Halide **Lamp Life:** 10,000 hours average **Color Temperature:** 4,000°K

**Cool Down:** 2-3 Minute re-strike period

**Power Consumption:** 200 Watts Maximum **Continuous Load:** 120VAC 60Hz Only. Start up 3 Amps / 1.8 Amps Running

**Dimensions:** 9.5" x 9.5" x 20" (241mm x 241mm x 508mm) **Weight:** 21 lb. (9.5 kg)

**Operating Temperature Range:** Min. 20°F (29°C) Max. +110°F (+44°C)

**Construction:** • UV Stabilized Materials. Water, corrosion and chemical resistant

**Fiber Capacity:** Max. 500 x 0.75mm or 288 x 1.0mm PMMA end light fibers / 756 x 0.75mm or 400 x 1.0mm with optional ferrule upgrade kit

**Control:** 1 RPM Synchronous motor. Wireless Remote option available. Synchronous model allows all units powered by same line voltage circuit to automatically synchronize without an additional controller.

**Standard Features:** On/Off Power and color wheel switches

**Color Wheel:** 6 positions Color Wheel included. **Colors:** White, Lime Green, Cyan, Dark Blue, Magenta, Orange

**Ventilation:** 115 CFM enclosure cooling ,28 CFM fiber tunnel cooling Recommended distance from surface, 6"

**Mounting:** Surface or burial mount up to area below fan location. Can be set right into landscaping.

**Acoustic Rating:** 48dB(A) **IP Rating:** 23 **Warranty:** 2 year, excluding lamp **Certs:** UL , ULc Listed, Wet Location

**Ordering Info:**

Stock No.	Description
150T	150W M-Halide Tower Non-Sync
150TS	150W M-Halide Tower Sync
756EK	Fiber Expansion Kit 150T
TRemote	Wireless Remote Kit

**Vivid Light Design**

1322 W. Collins Ave., Orange, CA 92867 • E-mail: [info@vividlightdesign.com](mailto:info@vividlightdesign.com) • [www.vividlightdesign.com](http://www.vividlightdesign.com)

Tel: (714) 322-3996 • Copyright © 2011 Vivid Light Design. All Rights Reserved